













6/12/24V AUTOMATIC 40 AMP 8 STAGE BATTERY MANAGER

PART NO HDBM4000

Perfect for the modern professional workshop, the Battery Manager has the power and functions needed for today's high tech vehicles. Engineered and manufactured by leading European charger specialist Telwin, it boasts the very latest in battery management. Supplied standard with removable leads and the option of extended leads if needed.

FEATURES

Multi-Voltage Operation

Adjustable to suit 6, 12 or 24 Volt operation

Customise Charge Profile

Adjustable output for different battery sizes and chemistry type selection to suit Wet, Calcium, AGM and Gel

Testing & Diagnostics

Sophisticated functions to accurately test a vehicles alternator for faults, starting capacity as well as measure voltage levels

Delivers a fast charge of 70A for 3 seconds (30 sec cycles) to start vehicles with a flat battery (subject to battery condition)

Maintains constant voltage allowing vehicle diagnostics or to retain settings during battery replacement

PART NO		HDBM400	HDBM4000			
ТҮРЕ		8 Stage A	8 Stage Automatic			
INPUT		240V, 50	240V, 50Hz, 600W			
ОИТРИТ		3-40A at				
			3–40A at 12V 3–20A at 24V			
		3-20A at	24V			
ENGINE START		12V only 7	12V only 70A for 3 secs			
CHARGE CONTROL			6V	12V	24V	
		Auto:	7.2V	14.4V	28.8\	
		Auto•:	7.7V	15.4V		
		Gel:	7.2V	14.4V	28.8V	
		AGM:	7.35V	14.7V	29.4\	
		Wet:	7.7V	15.4V	30.8V	
		Calcium:	8.0V	16.0V	32.0\	
FLOAT VOLTAGE			6.7V	13.5V	27.0\	
MINIMUM START VOLTAGE				2.0V		
BACK DRAIN			20mA	50mA	80m	
APPROVALS		Electrical	Electrical Safety, EMC			
BATTERY CHARGE TIMES						
HDBM4000	6 & 12V BATTERY RANGE	24V BATTERY RANGE	BATTERY		CHARGE TIME	
AUTOMOTIVE (CCA)	100-3700	100-2000	100-2000		6–15 hrs	
MARINE (MCA)	120-4600	120-2300	120-2300		8–18 hrs	
DEEP CYCLE (AH)	14-600	14 200	14–300		7–17 hrs	

