
IC100L | INTELLI-CHARGE

12V AUTOMATIC BATTERY CHARGER

The ideal charger for maintaining infrequently used vehicles such as motorcycles, jet skis and ride on mowers.



4



5 STAGE

1 AMP



www.a1batterypro.com.au

SPECIFICATIONS

PART NO.	IC100L
TYPE	5 Stage Automatic
INPUT	240VAC, 50Hz, 20W
OUTPUT	12V
OUTPUT CURRENT	1A
MINIMUM START VOLTAGE	2.0V
BACK DRAIN	1mA
APPROVALS	Electrical Safety, EMC
CHARGE VOLTAGE	14.2V
FLOAT	13.5V
L.E.D CHARGE INDICATION	
RED LIGHT ON	Power on, not charging
* RED LIGHT FLASHING	Fault
* GREEN LIGHT FLASHING	Charging
GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off

BATTERY CHARGE TIMES

	VOLTAGE	BATTERY SIZE	CHARGE TIME
AUTOMOTIVE	12V	100-320CCA	2–10hrs
DEEP CYCLE	12V	2–10Ah	2–10hrs
LITHIUM	12V	2–10Ah	2–10hrs





KEY FEATURES

COMPREHENSIVE KIT Supplied battery clamps and a fused vehicle harness provide charging options

FUSED WIRING HARNESS 0.6m harness allows permanent connection and features polarity protection

3 PIN ELECTRICAL PLUG Plugs directly into standard electrical outlet

SAFER CHARGING Spark free and polarity protected

L.E.D INDICATOR Displays charge status











