IC7W | INTELLI-CHARGE

12V AUTOMATIC WORKSHOP BATTERY CHARGER

Offering all the features of its standard 7A counterpart, this sophisticated and compact charger is supplied with protective rubber moulded end caps for enhanced durability, ideal for the rigours of workshop environments.

7 STAGE **7 AMP**

APPLICATION GUIDE

















www.a1batterypro.com.au

KEY FEATURES

MULTI-CHEMISTRY

Set the charging profile to suit battery chemistry type: Wet, Calcium, AGM, Gel or Lithium



Adjustable for different battery sizes for precise charging

POWER SUPPLY MODE

Retains vehicle computer settings when changing a battery or can run 12V appliances

SAFER CHARGNG

Spark free and polarity protected connection

SHOCK & DUST PROOF

Durable construction with rubber moulded end caps for the toughest workshop conditions











SPECIFICATIONS

PART NO.	IC7W
TYPE	7 Stage Automatic
INPUT	240VAC, 50Hz, 110W
OUTPUT	12V
OUTPUT CURRENT	1, 2, 4, 7A
MINIMUM START VOLTAGE	2.0V
BACK DRAIN	1mA
APPROVALS	Electrical Safety, EMC
CHARGE VOLTAGE	14.1V (GEL), 14.4V (AGM), 14.7V (WET), 16.0V (CALCIUM), 14.2V (LITHIUM)

L.E.D CHARGE INDICATION

• RED LIGHT ON	Power on
BLUE LIGHT ON	Charging
GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off

BATTERY CHARGE TIMES

	VOLTAGE	BATTERY SIZE	CHARGE TIME
AUTOMOTIVE	12V	40-800CCA	6-12 hrs
MARINE	12V	55-900MCA	8–15 hrs
DEEP CYCLE	12V	7–140Ah	6-20 hrs
LITHIUM	12V	2-70Ah	2–10 hrs





