# IC25W | INTELLI-CHARGE

# 12V AUTOMATIC WORKSHOP BATTERY CHARGER

Ideal for workshop environments, this powerful charger features protective rubber moulded end caps for superior durability. It offers all the features of its standard 25A counterpart without the remote control and temperature compensation probe.

7 STAGE 25 AMP

#### **APPLICATION GUIDE**

















www.a1batterypro.com.au



## **KEY FEATURES**

### MULTI-CHEMISTRY

Set the charging profile to suit battery chemistry type: Wet, Calcium, AGM, Gel or Lithium



Adjustable for different battery sizes for precise charging

#### POWER SUPPLY MODE

Maintains a constant voltage on a battery making it ideal for vehicle diagnostics

#### SAFER CHARGING

Spark free and polarity protected connection

# SHOCK & DUST PROOF

Durable construction with rubber moulded end caps for the toughest workshop conditions











## **SPECIFICATIONS**

PART NO.	IC25W
TYPE	7 Stage Automatic
INPUT	240VAC, 50Hz, 450W
OUTPUT	12V
OUTPUT CURRENT	2, 6, 12, 25A
MINIMUM START VOLTAGE	2.5V
BACK DRAIN	3mA
APPROVALS	Electrical Safety, EMC
CHARGE VOLTAGE	14.1V (GEL), 14.4V (AGM), 14.7V (WET), 16.0V (CALCIUM), 14.2V (LITHIUM)


#### L.E.D CHARGE INDICATION

SCREEN	Back lit LCD screen
• RED LIGHT ON	Power on
BLUE LIGHT ON	Charging
• GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off

#### **BATTERY CHARGE TIMES**

	VOLTAGE	BATTERY SIZE	CHARGE TIME
AUTOMOTIVE	12V	80-3000CCA	7–24 hrs
MARINE	12V	110-4200MCA	7–24 hrs
DEEP CYCLE	12V	14-500Ah	7–24 hrs
LITHIUM	12V	4-250Ah	2-10 hrs







REPLACEMENT PARTS: **BC100R** 100A Clamp – POS **BC100B** 100A Clamp – NEG OPTIONAL ACCESSORIES: **ICTEMP-5M** Temperature Compensation Lead 5m long **ICTEMP** Temperature Compensation Lead 1.8m long **ICREMOTE-1** Remote Control **ICLEAD-10M** 10m Extension lead for ICREMOTE-1