



Cleo

HANDHELD LITHIUM SOLAR GENERATOR



416Wh

Storage Capacity

300W

Max Output

600W

Surge Output

120W

Solar Input

An ideal power-partner for outdoor, remote and off-grid scenarios such as camping, travelling or blackouts.



Lithium-ion



Lightweight



Silent



LED Torch

Take and generate power with you anywhere.



Power Your Essentials

On top of charging your smaller devices, Cleo will keep medium appliances running—including your coffee machine, TV, desktop computer, fans, and more.



Portable, Silent & Safe

Cleo is a compact, lightweight and noise-free battery that can be easily carried by hand. Free from emissions, with a reliable lithium battery system and advanced circuit design, Cleo is safe for even indoor use.

Charge Anywhere

Gain full energy independence and charge Cleo literally anywhere using the corresponding solar panel. You can also charge it via adaptor (plug-in to the wall), car charger or external generator.

Battery Storage & Output

Cleo has a 416Wh storage capacity, with 300 watts output to power appliances via AC(x2), DC, 12V & USB-A 5V.

LED Torch

Light up the darkness with a bright LED torch function with three levels of brightness (High-Med-Low).

User-friendly & Long-Lasting

Cleo is tough—built for the rugged outdoors—but also easy to operate with a simple interface. Charge and go with zero setup.

1 Year Warranty Included

What's in the box?



Cleo



AC Adapter



Solar Charging Cable (DC)



AC Charging Cable



User Manual

Cleo Technical Specifications

Battery	Rated Capacity	416Wh
	Rated Voltage	11.1V (9.6-12.6Vdc)
	Battery Cell Type	Lithium-ion
AC Output	Rated Output Power	300W Pure Sine Wave
	Peak Surge Output	600W
	Output Voltage	220V-240Vac
	Output Frequency	50Hz/60Hz (adjustable)
DC Output	Overload Ability	100% (1sec), 50% (2min)
	Cigarette Lighter Output	12V, 10A
	DC5521 Output	(2x) 9.6V-12.6V, 3A
Solar PV Input	USB Output	(2x) 5V, 3A + (2x) QC - BC1.2
	Type-C Output (PD45W)	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (QC - PD2.0)
	Max Input Power	120W
Charge Time	MPPT Input Voltage	14-40Vdc
	Charge Time	4 Hours (120W)
LED Torch	AC Wall Charge	5-6 hours (80W)
	DC Car Charge	9 hours (48W)
General	Brightness	High - Medium - Low
	Working Environment Condition	Temperature: 0-45°C (Charge), 0-60°C (Discharge)
Protection	Product Size	300mm (L) x 159mm (W) x 219mm (H)
	Net Weight	6.2kg
	IP Rating	IP21



Made in Melbourne

Proudly Support local Australian industry when you purchase SR Portable products.

Get Local Support

Have peace of mind knowing you can talk to a local supplier for all product inquiries and warranty support. Talk to us for more details.