ACOO8 | CHARGE N' MAINTAIN

12V AUTOMATIC BATTERY CHARGER

Ideal for maintaining infrequently used vehicles such as motorcycles, jet skis and ride on mowers.

4 STAGE 0.8 AMP

APPLICATION GUIDE









KEY FEATURES

FULLY AUTOMATIC

Simply connect and forget, no risk of overcharging, maintains battery ready for use



SAFE & SIMPLE

Spark-free and polarity protected, safe to use while the battery is still in the vehicle



FUSED WIRING HARNESS

Quick-connect fused wiring harness for permanent installation (BCWH)



Batterypro www.a1batterypro.com.au

SPECIFICATIONS

OI LOII IOATTOTO	
PART NO.	AC008
TYPE	4 Stage Automatic
INPUT	100VAC-240VAC, 50-60HZ
OUTPUT	12V
OUTPUT CURRENT	0.8A
MINIMUM START VOLTAGE	2.0V
BACK DRAIN	<1.0mA
APPROVALS	Electrical Safety, EMC
IP RATING	IP65

L.E.D CHARGE INDICATION

* GREEN LIGHT FLASHING	Charging Stage
GREEN LIGHT ON	Fully Charged
AMBER LIGHT ON	Fault

BATTERY CHARGE TIMES

			•
	VOLTAGE	BATTERY SIZE	CHARGE TIME
AUTOMOTIVE	12V	100-350CCA	Maintenance
MARINE	12V	150-400MCA	Maintenance
LITHIUM (LiFePO ₄)	12V	1-8Ah	1-10hrs





