BATTERY DATA SHEET





М	IF MAINTENANCE FREE	
BATTERY	REF BTX	14AHL-BS
		12v VOLTAGE-v
BTX14AHL-BS		12.6Ah CAPACITY - Ah (20Hr)
Pb Pb recommendation (Sale B) (Pr)		12Ah CAPACITY - Ah (10Hz)
TECHNOLOGY		DIMENSIONS
 AGM construction (absorbed acid) VRLA battery (Valve Regulated Lead Acid) 	Length (A): Width (B):	133±2mm 90±2mm
Supplied with a separate acid packHomologated by OEM	Container height: Total height (C):	164±2mm 164±2mm
FEATURES		
Upright installation onlyMaintenance free (no water refilling)		
 Sealed after filling, no gas emission through venting hole (under normal operation) 		
 High power Does not need to be recharged while stocked 		(C)
 Suitable for cold weather Reduction of plate sulfation 	90mm	
 Higher life cycle (up to three times longer than conventional batteries) 	(B)	133mm (A)
Longer voltage hold	_	TERMINALS
UPGRADE FOR		
-		\$6.4
WEIGHT Battery (with acid): Application	oprox 4.71kg	0.6
MOUNTING ANGLE	FR01	NT SIDE
90° Medium inclinaison	90° TOF	\$\$6.4
f 🞯 🖿 🖬 🛛 BS BATTERY	www.bs-battery.com	sales@bs-battery.com