

SCO15 | EVERYDAY CONTROLLER

4 STAGE AUTOMATIC SOLAR CHARGE CONTROLLER

A compact controller suitable for solar panels producing up to 15 Amps. Utilising an advanced 4 stage charging profile, this controller ensures both starting and deep cycle batteries are kept in peak condition.

15 AMP

OLAR PANELS CONTROLLERS



KEY FEATURES

L.E.D CHARGE INDICATOR

Displays quick reference to charge status of the battery



Potted circuit board and plated terminals protect controller from the elements

EASE OF CONNECTION

Plated screw termination and quick reference label



MULTI-CHEMISTRY

Set the charging profile to suit battery chemistry type: Wet, Calcium, AGM or Gel



SPECIFICATIONS

PART NO.	SC015		
INPUT	12V		
MAX INPUT	25Vdc, 15A		
MAX CHARGE	15A		
MAX PANEL SIZE	180W (12V)		
BATTERY	12V		
CHARGE CONTROL	4 Stage Charging		12V
	Bulk:		14.0V
	Absorption:	Gel:	14.1V
		AGM:	14.4V
		Wet:	14.7V
		Calcium:	14.9V
	Equalisation:		15.5V
	Float:		13.6V
APPROVAL	EMC		
IP RATING	IP65		



