



200W

MONOCRYSTALLINE FOLDABLE SOLAR PANEL

Generate power anywhere, anytime, on all your outdoor expeditions with this ultra-portable solar panel.

200W

18V/5A Max Output

8kg

Weight

IPX4

IP Rating



Solar Power



Lightweight



Waterproof



Foldable



High Efficiency



AUSTRALIAN MADE

Take and generate power with you anywhere.



Portable Power

These portable foldable panels can be carried anywhere easily to generator solar power anywhere, anytime. They can be stored for extended periods of time and are easily deployed when solar power is required during outdoor excursions, vacations or during emergency backup power.

Foldable & Compact

Weighing in at 8kg, the 200W foldable solar panel is portable and easy to carry using its own handle and bracket. Once folded, it measures 58.5cm x 56.5cm x 5cm, and once opened, 224cm x 56.5cm x 0.3cm.

Robust and Durability

Made with PET (for higher transmission efficiency), EVA resin encapsulation (for better protection of modules) and a weather resistant film. The panel can operate in a range of temperatures between -40°C to 80°C.

Power Info

200W solar panel (18V/5A max output) with a 10 year power output warranty.

Quality Components

Panels are made of Monocrystalline and a sturdy ultra-cleared tempered that gives 24% cell efficiency.

1 Year Warranty Included

What's in the box?



200W Solar Panel



MC4 Connector

Compatible with the Minotaur Solar Generator



Technical Specifications

| | |
|---------------------------------|---------------------------------------|
| Maximum Power | 200W |
| Solar Cell Type | Monocrystalline |
| Cell Efficiency | 21.4% |
| Maximum Operating Current (Imp) | 10.7A |
| Maximum Power Voltage (Vmpp) | 18.7V |
| Open Circuit Voltage (Voc) | 22.1V |
| Short Circuit Voltage (Isc) | 11.21A |
| Output Tolerance Wattage | ± 3% |
| DC Output Connector | DC5521 x1 or Other Type |
| DC Output Current | 18V 5A Max |
| USB-A Output | 5V 3A (Optional) |
| USB-A Output | QC3.0 5V/3A 9V/2A 12V/1.5A (Optional) |
| IP Rating | IPX4 |
| Working Temperature | -40 C ~ 80 C |
| Expanded Size | 12240x565x3mm |
| Foldable Size | 585x565x50mm |
| Net Weight | 8kg |
| Protection Rating | IPX4 |

Designed in Australia

Proudly support local Australian industry when you purchase SR Portable products.

Get Local Support

Have peace of mind knowing you can talk to a local supplier for all product inquiries and warranty support. Talk to us for more details.

Distributed by Powertech Energy

www.powertechenergy.com.au

1300 078 324 | sales@powertechenergy.com.au

