



IC25RV | INTELLI-CHARGE

12V AUTOMATIC RV BATTERY CHARGER

The ideal charger for direct RV fitment. Delivering a sophisticated charge and multi-chemistry profile selection, this ultra robust 25A unit is engineered to handle the rigours of on and off-road in-vehicle permanent installation.



Batterypro

www.a1batterypro.com.au

NEW

Temperature
Compensation Lead

APPLICATION GUIDE

NOW
LITHIUM
COMPATIBLE

KEY FEATURES

MULTI-CHEMISTRY

Set the charging profile to suit battery chemistry type: Wet, Calcium, AGM, Gel or Lithium



ADJUSTABLE OUTPUT

Adjustable for different battery sizes and includes 5m temperature compensation lead for precise charging



DIRECT INSTALLATION

Supplied with 1.5m length terminated leads for permanent fitment to RV



WIRED REMOTE CONTROL

Allows charger to be mounted out of sight yet retain total control, includes 10m lead



SHOCK & DUST PROOF

Durable construction with a dust and shock proof body this charger has spark free and polarity protected connection



REPLACEMENT PARTS: ICLEAD-10M 10m Extension lead for ICREMOTE-1 ICREMOTE-1 Remote Control ICTEMP-5M Temperature Compensation Lead 5m long

OPTIONAL ACCESSORIES: ICTEMP Temperature Compensation Lead 1.8m long BC100R 100A Clamp – POS BC100B 100A Clamp – NEG

SPECIFICATIONS


PART NO.	IC25RV
TYPE	7 Stage Automatic
INPUT	240VAC, 50Hz, 450W
OUTPUT	12V
OUTPUT CURRENT	2, 6, 12, 25A
MINIMUM START VOLTAGE	2.5V
BACK DRAIN	Charger 3mA, 4mA with remote
APPROVALS	Electrical Safety, EMC
CHARGE VOLTAGE	14.1V (GEL), 14.4V (AGM), 14.7V (WET), 16.0V (CALCIUM), 14.2V (LITHIUM)

L.E.D CHARGE INDICATION

SCREEN	Back lit LCD screen
• RED LIGHT ON	Power on
• BLUE LIGHT ON	Charging
• GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off

BATTERY CHARGE TIMES

	VOLTAGE	BATTERY SIZE	CHARGE TIME
AUTOMOTIVE	12V	80–3000CCA	7–24 hrs
MARINE	12V	110–4200MCA	7–24 hrs
DEEP CYCLE	12V	14–500Ah	7–24 hrs
LITHIUM	12V	4–250Ah	2–10 hrs

5
YEAR
WARRANTY

ICREMOTE-1

