



## **SPECIFICATIONS**

## 12V DC POWER MANAGEMENT BOARD WITH INVERTER ICB2000-HD



## **DESCRIPTION**

A premium pre-built all-in-one DC power board, an ideal solution tailored for ute canopies and caravan applications. Designed for effortless fitment, this unit comes pre-wired, ensuring a swift and professional installation.

With essential features such as a DC-DC charger, 2000W pure sine wave inverter, 200Ah Lithium battery, battery monitor, sockets & switches panel, heavy-duty output battery connectors, and circuit protection, this power board offers a comprehensive and convenient power management system for all your electrical needs.

Complex installations are a thing of the past, embrace the simplicity and efficiency of this all-in-one power solution with ICB2000-HD.

## **FEATURES AND BENEFITS**

- Pre-wired for easy installation
- All-in-one solution

|                 | 12V AUTOMATIC BATTERY CHARGER              |   |  |
|-----------------|--|---|--|
|                 | PART NO.                                   | IC50  |  |
|                 | TYPE                                       | 7 Stage Automatic                           |  |
|                 | ALTERNATOR INPUT VOLTAGE                   | 240VAC, 50Hz, 820W                          |  |
|                 | OUTPUT CURRENT                             | 2, 6, 12, 25, 50A                           |  |
|                 | BATTERIES SUPPORTED                        | Gel, AGM, Calcium, Lithium                  |  |
|                 | DC/SOLAR CHARGER                           |   |  |
|                 | PART NO.                                   | IDC25X                                      |  |
|                 | CHARGE TYPE                                | 5 Stage                                     |  |
|                 | ALTERNATOR INPUT VOLTAGE                   | 9-32Vdc                                     |  |
|                 | MAX SOLAR INPUT                            | 360W  |  |
|                 | OUTPUT CURRENT                             | 11-32Vdc 25A                                |  |
|                 | BATTERIES SUPPORTED                        | Gel, AGM, Calcium,<br>Lithium, User Defined |  |
|                 | BATTERY MONITOR                            |   |  |
|                 | PART NO.                                   | LBM-BT                                      |  |
| l               | INPUT VOLTAGE                              | 6.5~16Vdc                                   |  |
|                 | BATTERY CAPACITY                           | 10~10,000Ah                                 |  |
|                 | IP RATING                                  | IP20  |  |
|                 | WORKING TEMPERATURE                        | -20°C~65°C                                  |  |
| LITHIUM BATTERY |  | ATTERY                                      |  |
| ٧               | PART NO.                                   | LB200-HD                                    |  |
|                 | NOMINAL VOLTAGE                            | 12.8V                                       |  |
|                 | NOMINAL CAPACITY                           | 200Ah                                       |  |
|                 | MAXIMUM CHARGE<br>CURRENT                  | 100Amps                                     |  |
|                 | MAXIMUM DISCHARGE<br>CURRENT               | 200Amps                                     |  |
|                 | MAXIMUM NUMBER OF<br>BATTERIES IN PARALLEL | 4   |  |
|                 | NUMBER OF<br>DISCHARGE CYCLE               | 2000  |  |
|                 | BOARD DIMENSIONS                           | 1000 x 493 x 190mm                          |  |
|                 |  |   |  |





