

SPECIFICATIONS	EF5500FW
Type	Condenser
Rated Voltage	230V
Frequency	50Hz
Rated Output	4500 Watts
Max Output	5500 Watts
DC Output	None
Engine Type	OHV MZ360 Air Cooled
Displacement	357cc
Max Output	8.8kW (12hp) @4000rpm
Starting System	Recoil
LxWxH (mm)	670x535x565
Dry Weight	80kg
Fuel Tank Capacity	28L
Operating Hours (1/4 Load)	17.5hr (Eco On)
Noise Level (1/4 Load)	71dBA (7m)
Noise Level (Full Load)	96.6dBA (7m)
Brushless Alternator	•
Auto Decompressor	•
Electric Starter	
Circuit Breaker	Non-Fused
Fuel Level Gauge	•
Oil Level Warning	•
Voltage Meter	•
Pilot Lamp	
Noise Block™	
Economy Idle Control	
Twin Tech™ (Parallel Use)	
Transportation Kit	Optional
Remote Starter Kit	
AC Plug	•
DC Charging Cord	

## EF5500FW

### 5.5KVA PETROL POWERED GENERATOR

The EF5500FW boasts a powerful environmentally friendly 12 hp engine, 2 x 15 Amp outlets and a circuit breaker, 28-litre long range fuel tank that will run continuously for up to 17.5 hours (Eco on at 1/4 load) and an extra large muffler for super quiet operation. Great for the tradie and for industrial use.

#### KEY FEATURES

- 4-Stroke OHV Engine
- Non-Fused Circuit Breaker
- Long Range Fuel Tank
- Brushless Alternator
- Oil Warning System
- Fuel Gauge
- Independent Fuel Tap
- Voltage Meter

CONVENTIONAL GENERATORS



**4 YEAR WARRANTY**

Overseas model shown with accessories fitted.

