



# Batterypro

*The Big Blue Buildings  
Mackay & Townsville*

Mackay Store: 07 4957 6123  
Townsville Store: 07 4774 7344  
E: quotes@a1batterypro.com.au

## LG18X1

18kVA Generator 240V 75Amps - Single  
Phase



- ALL NEW CABINET DESIGN
- 18 kVA 240 Volt
- Water Cooled
- MineSpec Bundled
- Silenced 65dB at 7 metres
- 3 × 15amp 240volt outlets
- Australian Compliant with RCD's
- Easy connect ATS plug
- Remote Start Systems Available

## Specifications

If disaster strikes and you are left high, dry, and powerless you'd want the very best in off-mains power. Our 18kVA Diesel Generator fits the bill. This generator provides clean mains-type power thanks to its 4-pole brushless alternator with AVR!

It's economical, reliable, sturdy, easy to use, and safe as houses. It will be business as usual no matter what the harsh conditions. Heat? Easy. Cyclone? Sorted. Time is money and you won't lose any of either with our time-proven reliable ABLE 18kVA Genset.

### Key Features:

- **Reliable Engine:** Equipped with our time-proven reliable OEM 4 Cylinder Diesel engine
- **Robust Design:** Tough-built, super-silenced, weather-resistant canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 20 Hours Continuous stable power at prime load. Its low 1500 RPM engine generates a more stable operation.
- **Silent Operation:** 65dbA at 7 metres, just similar to a normal conversation.
- **Clean Mains-Type Power:** Thanks to our 4-pole brushless synchronous alternator with AVR
- **Fuel efficiency:** Diesel fuelled - 4.5 Litres/Hour at prime load. Low fuel consumption. Low cost. A savings you can't ignore!
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **Easy to Use:** The straightforward digital control panel makes the generator easy to use.
- **Easy Transportability:** Designed with forklift slots for easy transportation.

Prime Power : 18kW / 18kVA 240 Volts 75Amps  
 Standby Power : 20kW / 20kVA  
 Power Factor : 1  
 Phase Voltage : Single Phase 240 Volt  
 Frequency : 50 Hertz  
 Engine : OEM 4 Cylinder Diesel  
 RPM : 1500/min  
 Cooling Method : Water Cooled - Rated For Australia's North  
 Alternator : Single Phase 4 Pole Brushless Synchronous -/c AVR  
 Starter System : 12-volt Electric - Battery Included  
 Controller : Comap MRS11  
 2 Wire / Remote Start Capable  
 Over Temperature Protection  
 Over Current Protection  
 Low Oil Protection  
 Safety Systems : Battery Isolator  
 Emergency Stop  
 Failsafe Shutdown Fuel Solenoid  
 Noise Level : 65 dBA at 7 metres  
 Fuel Tank Capacity : 90 Litres (-/c Fuel Gauge)  
 Running Time : 20 Hours Continuous (prime load)  
 Fuel Consumption : 4.5 litres/hour (prime load)  
 Chassis Enclosure : Lockable  
 Sound Deadening Throughout  
 Weather-Resistant Powder Coating  
 Stainless Steel Fittings  
 External Use  
 Mine Site Ready Bunding : Yes  
 ATS (Mains Failure) : Easy Connect Plug (ATS Box Optional)  
 Single Phase Outlets : 3 x 15 Amp IP66  
 Three Phase Outlets : No  
 Hardwire Terminals : Yes  
 RCD / RCBO : Australian Standard (IP67 Enclosed)  
 Options : Automatic Start Systems  
 GSM  
 Timer  
 Wireless Remote  
 Solar System Compatible (Majority)  
 ATS (Mains Failure Detection / Auto Transfer Switch)  
 Minespec Padlockable Battery Isolator  
 Weight : 770 kg  
 Dimensions : 167 L x 76 W x 117 H cm