



Batterypro

*The Big Blue Buildings
Mackay & Townsville*

Mackay Store: 07 4957 6123
Townsville Store: 07 4774 7344
E: quotes@a1batterypro.com.au

LG9D1

10kVA Generator 240V 37Amps Single
Phase, MineSpec Bunded



- ALL NEW CABINET DESIGN
- 10 kVA 240 Volt
- 3 cylinder diesel engine
- MineSpec Bunded
- Water Cooled
- Low rev 1500rpm engine for longer life
- Silenced 65dB at 7 metres
- 3 × 15amp 240volt outlets
- Australian Compliant with RCD's
- Easy connect ATS plug
- Remote Start Systems Available

Specifications

Powered by a low RPM time-proven reliable OEM 3 cylinder diesel engine with single phase four pole synchronous alternator. The ABLE 10kVA, 240V diesel generator is economical, efficient, silent, and robust, ideal for commercial, industrial, or construction power solutions. With a noise level that's just similar to a normal conversation, It can also be perfect as backup power for homes and offices.

Key Features:

- **Reliable Engine:** Equipped with our time-proven reliable OEM 3 Cylinder Diesel engine
- **Robust Design:** Tough-built, super-silenced canopy designed for outdoor.
- **Watercooled:** So it will run and withstands extremely hot conditions while it also extends the life of the engine over time.
- **Stable Operation:** 27 Hours Continuous stable power at prime load. Its low 1500 RPM engine generates a more stable operation.
- **Silent Operation:** A mere 65db at 7 metres, just similar to a normal conversation.
- **Fuel efficiency:** Diesel fuelled - 2.2 Litres/Hour at prime load. Low fuel consumption. Low cost. A savings you can't ignore!
- **Highest Safety Standards:** Australian Safety Standards compliant.
- **Easy to Use:** The digital control panel makes the generator easy to use.
- **Easy Transportability:** Designed with forklift slots for easy transportation.

Prime Power : 9kW / 9kVA 240 Volts 37Amps
 Standby Power : 10kW / 10kVA
 Power Factor : 1.0
 Phase Voltage : Single Phase 240 Volt
 Frequency : 50 Hertz
 Engine : OEM 3 Cylinder Diesel
 RPM : 1500/min
 Cooling Method : Water Cooled - Rated For Australia's North
 Alternator : Single Phase 4 Pole Brushless Synchronous -/c AVR
 Starter System : 12 volt Electric - Battery Included
 Controller : Comap MRS11
 2 Wire / Remote Start Capable
 Over Temperature Protection
 Over Current Protection
 Low Oil Protection
 Safety Systems : Battery Isolator
 Emergency Stop
 Failsafe Shutdown Fuel Solenoid
 Noise Level : 65 dBA at 7 metres
 Fuel Tank Capacity : 60 Litres (-/c Fuel Gauge)
 Running Time : 27 Hours Continuous (prime load)
 Fuel Consumption : 2.2 litres/hour (prime load)
 Chassis Enclosure : Lockable
 Sound Deadening Throughout
 Weather Resistant Powder Coating
 Stainless Steel Fittings
 External Use
 Mine Site Ready Bunding : Yes
 ATS (Mains Failure) : Easy Connect Plug (ATS Box Optional)
 Single Phase Outlets : 3 x 15 Amp IP66
 Three Phase Outlets : No
 Hardwire Terminals : Yes
 RCD / RCBO : Australian Standard (IP67 Enclosed)
 Options : Automatic Start Systems
 GSM
 Timer
 Wireless Remote
 Solar System Compatible (Majority)
 ATS (Mains Failure Detection / Auto Transfer Switch)
 Minespec Padlockable Battery Isolator
 Weight : 600 kg
 Dimensions : 141 L x 72 W x 111 H cm