BATTERY DATA SHEET





LITHIUM

LITHIUM (LiFePO4) | High Performance

REF BSLi-13



12_V VOLTAGE

96wh ENERGY

560_A CCA - A (EN)

TECHNOLOGY

- · Lithium Iron Phosphate cells construction
- Pre-charged batteries
- Homologated by OEM

FEATURES

- Fast charging
- Multi-positionning mounting
- Very safe and environmental friendly
- · Extensive cycle life: over 2000 cycles
- Very low self-discharge
- Cold temperature performance
- · Waterproof design
- Ready to use: just plug and play
- Robust brass terminals
- Heat resistance: up to 230°C
- Lighter weight

OPERATING TEMP. RANGE


Charge temperature: Discharge temperature: Storage temperature: 0°C to 45°C -20°C to 55°C 0°C to 30°C

DIMENSIONS & WEIGHT

Length (L): Width (W): Height (H): Weight: 183mm ±1mm 79mm ±1mm 170mm ±2mm 1.980kg (tolerance ±3%)








TERMINALS (mm)

Rubber Cap M6X14 Screws Spacer

REPLACEMENTS

SLA 51913

MOUNTING ANGLE



NON-SPILLABLE

Two Great Stores to choose from...

7 Cemetery Rd, Mackay QLD 4740 Phone 07 4957 6123 Unit 16, 547 Woolcock St, Mt Louisa, Townsville QLD 4814 Phone 07 4774 7344