

BLUETTI AC240P Portable Power Station | 2,400W 1,843Wh

Industry-Leading IP65 Water & Dust-resistant
2,400W AC Output / 3,600W Power Lifting Mode
Expandable up to 10,443Wh with 4 B210P batteries
1,200W Max. Solar Input
Smart Control & Monitor in BLUETTI App via Bluetooth & WiFi
Seamless UPS in 15ms



Specifications

BATTERY INFO

Capacity:	1,843Wh (51.2V, 36Ah)
IP Rating:	IP65
Type:	LiFePO ₄ (Lithium Iron Phosphate)
Life Cycles:	3,500+ Cycles to 80% Original Capacity(Silent Mode)
Shelf-life:	Recharge to 40%-60% Every 3-6 Months
Management System:	MPPT Controller, BMS, etc



OUTPUT

AC Outlets: 4 X 230V/11A Outlets

2,400W In Total

Inverter Type: Pure Sine Wave

Power lifting Mode: 3,600W

USB-C Port: 2 x 100W Max.

USB-A Port: 2 x 18W USB-A

RV Port: 12VDC/30A, 360W Max.

Cigarette Lighter Port: 1 x 12V/10A

*All Regulated.

INPUT

AC Input: 2,400W Max.

Solar Input: 1,200W Max., 11V-60VDC, 21A

Car Input: 12/24V from Cigarette Lighter Port

Max Input: 2,400W, with AC + Solar Input

RECHARGE TIME

AC charging: 2,400W Max.(0%-80% in 45 minutes)

Solar (1,200W): 0–100% in 1.5 Hours 1,200W (With prime

sunshine, ideal orientation and low temperature)

12V/24V Car Outlet (100W/200W): $\approx 0-100\% 14.6 \text{ Hours} (12V)$

0-100% 7.3 Hours (24V)



GENERAL

Scalability:	Expandable w/ Up to 4 x B210P
Pass-through Charging:	Yes
Weight:	33kg / 72lbs
Dimensions (L x W x D):	419.5 × 293.5 × 409.5mm / 16.5 × 11.6 × 16.1in
Operating Temperature:	-4°F-104°F (-20°C-40°C)
Storage Temperature:	14°F-113°F (-10°C-45°C)
Certifications:	UL2743, UKCA, TELEC, RCM, FCC ID, CE, PSE, NTC
Warranty:	6 Years

^{*}Specifications are subject to change without further notice.

Width:

11.6inches(293.5mm)

Length:

16.5inches (419.5mm)

Height: 16.1inches (409.5mm)



Weight: About 33kg /72lbs



In The Box







Solar Charging Cable



Car Charging Cable



Grounding Screw



User Manual

Warranty Card



AC240P Portable Power Station